



SAFETY DATA SHEET

1. Identification

Product identifier	WROUGHT ALUMINUM PRODUCTS, 3xxx SERIES ALLOYS
Other means of identification	
SDS number	665
Version #	07
Revision date	March 8, 2015.
Synonym(s)	3xxx Series Alloys, 3xxx Cladding, 0033, 0346_DA3113, 3003, 3003F, 3003-C06C, 3005, 3103, 3104, 3104BLND, 3105, 3PORC, Alclad 3003, Alclad 3004, AM01, Clad 3003, C01S, C02D, C03H, C03Z, C04N, C05N, C06C, C06D, C06E, C06S, C06T, C08A, C08Z, C10H, C10T, C12H, C13C, C13P, C14P, C156, C15B, C15P, C162, C189, C18D, C19E, C1A8, C20B, C21H, C229, C22M, C23E, C23M, C24M, C24P, C25N, C26E, C26Z, C27E, C27H, C27P, C27Z, C28P, C29D, C29P, C2A3, C300, C30N, C30P, C31D, C31N, C32D, C32J, C32N, C32P, C33D, C33N, C33P, C34A, C34D, C34N, C35B, C35D, C35E, C35N, C35P, C36N, C37P, C38H, C38N, C38U, C39H, C40U, C42U, C430F, C434F, C43Z, C441F, C445F, C447F, C44R, C45K, C45Z, C469F, C46U, C46Z, C474F, C475, C47B, C47D, C47E, C47K, C47U, C483F, C48D, C48E, C48U, C49B, C49K, C50K, C50U, C517, C518, C519F, C51K, C51U, C52U, C53B, C53R, C547F, C548F, C54W, C55E, C55W, C568, C56A, C56K, C56R, C56W, C57E, C582F, C58B, C58E, C58H, C58W, C590F, C59B, C59E, * C604F, C60R, C612F, C615F, C616F, C617F, C61W, C628F, C63R, C63Z, C64R, C64Z, C70E, C70W, C71D, C71E, C720, C72D, C72E, C72W, C73D, C73E, C74U, C75U, C76H, C76S, C77A, C783, C784, C786, C788, C78C, C78R, C791, C793, C80S, C82C, C83C, C84C, C85Z, C87U, C88S, C91B, C91D, C92B, C93B, C94B, C94S, C94U, C95C, C96N, C98C, C98D, C98T, C99T, CH14, CK32, CP63, CU54, CZ88, DN3N, DA3103, DA3022, DA3118, HG321/0399, KB11, MC365, MC369, MC370, MC371, MC372 MC373, MC374, MC378, MC380, MC382, MC386, MC387, MC389, MC392, MC395, MC396, MC398, MC399, MC400, MC401, MC402, MC403, MC404, MC405, MC406, MC413, MC414, MC424, MC425, MD52, MD176, MD189, MD228, MD229, MD239, MD240, MD241, MD243, MD263RB, MD263RH, MD263RL, MD267, MD268, MD271, MD272, MD276, MD278, MD281, MD285, MD286, MD287, MD288, MD289, MD291, MD297, MD299, MD305, MD306, MD307, MD308, MD310, MD311, MD312, MD313, MD314, MD315, MD321, MD324, MD327, MD329, MD330, MD333, MD334, MD338, MD339, MD340, MD341, MD347, MD350, * MD351, MD352, MD354, MD355, MD356, MD357, MD359, MD360, MD362, MN363, MN381, MN397, MN421, MN422, MN423, MN427, MN428, RA108, RA135, RA169, RA173, RA190, RA203, RA211, RA220, RA236, RA240, RA245, RA254, RA258, RA259, RA261, RA263, RA264, RA269, RA270, Showa HG311, X301.
Recommended use	Various fabricated aluminum parts and products Fabricated aluminum parts and products
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	Alcoa Inc. 201 Isabella Street Pittsburgh, PA 15212-5858 USA Health and Safety Tel: 1-412-553-4649 Health and Safety Fax: 1-412-553-4822 Health and Safety Email: accmsds@alcoa.com
Emergency Information	CHEMTREC: +1-703-527-3887 +1-800-424-9300 (24 Hour Emergency Telephone, multiple languages spoken); ALCOA: +1-412-553-4001 (24 Hour Emergency Telephone, only English spoken)
Website	For a current Safety Data Sheet, refer to Alcoa websites: www.alcoa.com or internally at my.alcoa.com EHS Community

2. Hazard(s) identification

Classification

This product is considered not hazardous under 29 CFR 1910.1200 (Hazard Communication).

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.

OSHA defined hazards	Combustible dust
Label elements	
Hazard symbol	None.
Signal word	Warning
Hazard statement	The mixture does not meet the criteria for classification. May form combustible dust concentrations in air.
Precautionary statement	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Reuse or recycle material whenever possible. Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Non-combustible as supplied.
	Explosion/fire hazards may be present when: <ul style="list-style-type: none"> • Dust or fines are dispersed in air. • Chips, dust or fines are in contact with water. • Dust and fines are in contact with certain metal oxides (e.g., rust, copper oxide). • Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide). <p>If molten: Use dry sand to contain the flow of material. All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Allow the spill to cool before remelting as scrap.</p>
Specific hazards	Non-combustible as supplied. Small chips, fine turnings, and dust from processing may be readily ignitable.
	Explosion/fire hazards may be present when: <ul style="list-style-type: none"> • Dust or fines are dispersed in air. • Chips, dust or fines are in contact with water. • Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide).

3. Composition/information on ingredients

Composition comments Complete composition is provided below and may include some components classified as non-hazardous.

Mixtures

Components	CAS #	Percent
Aluminum	7429-90-5	>92
Zinc	7440-66-6	<2.8
Manganese	7439-96-5	<2
Silicon	7440-21-3	<1.9
Magnesium	7439-95-4	<1.6
Iron	7439-89-6	<1.1
Chromium	7440-47-3	<0.5
Nickel†	7440-02-0	<0.1
Lead‡	7439-92-1	<0.1

Additional Information † - Present as impurity. While Nickel is not intentionally added to this mixture, it could potentially enter through the recycle stream.
‡ - Present as impurity. While Lead is not intentionally added to this mixture, it could potentially enter through the recycle stream.
Additional compounds which may be formed during processing are listed in Section 8.

4. First-aid measures

Eye contact Dust and fumes from processing: Rinse eyes with plenty of water or saline for at least 15 minutes. If eye irritation persists: Get medical advice/attention.

Skin contact	Dust and fume from processing or contact with lubricant/residual oil: Wash with soap and water for at least 15 minutes. Get medical attention if irritation develops or persists.
Inhalation	Dust and fumes from processing: Remove to fresh air. Check for clear airway, breathing, and presence of pulse. If breathing is difficult, provide oxygen. Loosen any tight clothing on neck or chest. Provide cardiopulmonary resuscitation for persons without pulse or respirations. Consult a physician.
Ingestion	Not relevant, due to the form of the product.
Most important symptoms/effects, acute and delayed	Dust and fumes from processing: Can cause irritation of the upper respiratory tract. Additional health effects from elevated temperature processing (e.g., welding, melting): Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain. Contact with residual oil/oil coating: Prolonged skin contact may cause skin irritation and/or dermatitis.
Medical conditions aggravated by exposure	Asthma, chronic lung disease, and skin rashes.
General information	Dust and fume from processing: If exposed or concerned: get medical attention/advice.

5. Fire-fighting measures

Suitable extinguishing media	Use Class D extinguishing agents on fines, dust or molten metal. Use coarse water spray on chips and turnings.
Unsuitable extinguishing media	DO NOT USE halogenated extinguishing agents on small chips/fines. DO NOT USE water in fighting fires around molten metal. These fire extinguishing agents will react with the burning material.
Specific hazards arising from the chemical	May be a potential hazard under the following conditions: <ul style="list-style-type: none"> • Dust clouds may be explosive. Even a minor dust cloud can explode violently. Dust accumulation on the floor, ledges and beams can present a risk of ignition, flame propagation and secondary explosions. • Chips, fines and dust in contact with water can generate flammable/explosive hydrogen gas. These gases could present an explosion hazard in confined or poorly ventilated spaces. • Dust and fines in contact with certain metal oxides (e.g., rust, copper oxide). A thermite reaction, with considerable heat generation, can be initiated by a weak ignition source. • Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide). Moisture entrapped by molten metal can be explosive. Contact of molten aluminum with certain metal oxides can initiate a thermite reaction. Finely divided metals (e.g., powders or wire) may have enough surface oxide to produce thermite reactions/explosions.
Hazardous combustion products	None known.
Special protective equipment and precautions for firefighters	Firefighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing when appropriate.
Fire-fighting equipment/instructions	Use gentle surface application of Class D extinguishing agent or dry inert granular material (e.g., sand) to cover and ring the burning material. If impossible to extinguish, protect surroundings and allow fire to burn itself out.
General fire hazards	This product does not present fire or explosion hazards as shipped. Small chips, fine turnings, and dust from processing may be readily ignitable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Avoid generating dust. Avoid contact with sharp edges or heated metal. Molten, heated and cold aluminum look alike; do not touch unless you know it is cold. Use personal protection recommended in Section 8 of the SDS.
Evacuation procedures	Keep unnecessary personnel away.
Methods and materials for containment and cleaning up	Collect scrap for recycling. If molten: Use dry sand to contain the flow of material. All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Allow the spill to cool before remelting as scrap.
Environmental precautions	No special environmental precautions required.

7. Handling and storage

Handling	Keep material dry. Avoid generating dust. Avoid contact with sharp edges or heated metal. Hot and cold aluminum are not visually different. Hot aluminum does not necessarily glow red. Use personal protection recommended in Section 8 of the SDS.
Storage	Store in a dry place.

Requirements for Processes Which Generate Dusts or Fines

If processing of this product generates dust or if extremely fine particulate is generated, obtain and follow the safety procedures and equipment guides contained in Aluminum Association Bulletin F-1 and National Fire Protection Association (NFPA) codes and standards listed in Section 16.

Use non-sparking handling equipment, tools and natural bristle brush. Cover and reseal partially empty containers. Provide grounding and bonding where necessary to prevent accumulation of static charges during metal dust handling and transfer operations (See Section 15).

Local ventilation and vacuum systems must be designed to handle explosive dusts. Dry vacuums and electrostatic precipitators must not be used, unless specifically approved for use with flammable/explosive dusts (). Dust collection systems must be dedicated to aluminum dust only and should be clearly labeled as such. Do not co-mingle fines of aluminum with fines of iron, iron oxide (rust) or other metal oxides.

Do not allow chips, fines or dust to contact water, particularly in enclosed areas.

Good housekeeping practices must be maintained. Avoid all ignition sources. Dust accumulation on the floor, ledges and beams can present a risk of ignition, flame propagation and secondary explosions. Do not use compressed air to remove settled material from floors, beams or equipment

Requirements for Remelting of Scrap Material or Ingot

Molten metal and water can be an explosive combination. The risk is greatest when there is sufficient molten metal to entrap or seal off the water. Water and other forms of contamination on or contained in scrap or remelt ingot are known to have caused explosions in melting operations. While the products may have minimal surface roughness and internal voids, there remains the possibility of moisture contamination or entrapment. If confined, even a few drops of water can lead to violent explosions.

All tooling, containers, molds and ladles which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Any surfaces that may contact molten metal (e.g., concrete) should be specially coated.

Drops of molten metal in water (e.g. from plasma arc cutting), while not normally an explosion hazard, can generate enough flammable hydrogen gas to present an explosion hazard. Vigorous circulation of the water and removal of the particles minimize the hazards.

During melting operations, the following minimum guidelines should be observed:

- Inspect all materials prior to furnace charging and completely remove surface contamination such as water, ice, snow, deposits of grease and oil or other surface contamination resulting from weather exposure, shipment, or storage.
- Store materials in dry, heated areas with any cracks or cavities pointed downwards.
- Preheat and dry large items adequately before charging into a furnace containing molten metal. This is typically done by use of a drying oven or homogenizing furnace. The drying cycle should bring the metal temperature of the coldest item of the batch to 400°F (200°C) and then hold at that temperature for 6 hours.

Thermite explosions have been reported when aluminum alloys were melted in furnaces used for alloying with lead, bismuth or other metals with low melting temperatures. These metals, when added as high purity ingots, can seep through cracks in furnace liners and become oxidized. During subsequent melts in the furnace, molten aluminum can contact these metal oxides resulting in a thermite explosion.

Dross Handling

Small amounts of beryllium (<0.0002% or <2 ppm) can be present in aluminum alloys either from naturally occurring beryllium in aluminum ore or as a alloying element in the aluminum recycling stream. This beryllium does not present a health hazard during processing (grinding, cutting or welding) of aluminum products. However, beryllium may concentrate in the dross formed when aluminum scrap is remelted. Therefore, the potential for exposures to beryllium when handling dross must be considered. Control of airborne dust levels would be critical in reducing or eliminating this potential. For more information on the hazards associated with handling dross that contains beryllium, refer to Alcoa SDS No. 1013, Aluminum Dross with Low Beryllium. Copies of this SDS are available on www.alcoa.com or by calling +412-553-4649.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction Total dust
Chromium (CAS 7440-47-3)	TWA	1 mg/m ³	
Manganese (CAS 7439-96-5)	Ceiling	5 mg/m ³	Fume

U.S. - OSHA Components	Type	Value	Form
Nickel† (CAS 7440-02-0)	TWA	1 mg/m ³	
Silicon (CAS 7440-21-3)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust
Compounds Formed During Processing	Type	Value	Form
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	TWA	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
Chromium (II) compounds (CAS No. Not available)	TWA	0.5 mg/m ³	(as Cr)
Chromium (III) compounds (CAS No. Not available)	TWA	0.5 mg/m ³	(as Cr)
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	TWA	0.0025 mg/m ³	Action Level as Cr(VI))
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.0025 mg/m ³	Action Level as Cr(VI)
Iron oxide (CAS 1309-37-1)	TWA	10 mg/m ³	Fume.
Lead compounds, inorganic (CAS No. Not available)	TWA	0.05 mg/m ³	(as Pb)
		0.03 mg/m ³	Action Level (as Pb)
Manganese compounds, inorganic (CAS No. Not available)	Ceiling	5 mg/m ³	(as Mn) Fume
Nickel compounds, insoluble (CAS No. Not available)	TWA	1 mg/m ³	(as Ni)
Nitric oxide (CAS 10102-43-9)	TWA	30 mg/m ³	
		25 ppm	
Oil mist, mineral (CAS 8012-95-1)	TWA	5 mg/m ³	Mist.
Ozone (CAS 10028-15-6)	TWA	0.2 mg/m ³	
		0.1 ppm	
Zinc oxide (CAS 1314-13-2)	TWA	5 mg/m ³	Respirable fraction.
		5 mg/m ³	Fume.
		15 mg/m ³	Total dust.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value	Form
Lead‡ (CAS 7439-92-1)	TWA	0.05 mg/m ³	
Compounds Formed During Processing	Type	Value	Form
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	TWA	0.005 mg/m ³	as Cr(VI)
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	TWA	0.005 mg/m ³	
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.005 mg/m ³	as Cr(VI)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Compounds Formed During Processing	Type	Value	Form
Magnesium oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Nitrogen dioxide (CAS 10102-44-0)	Ceiling	9 mg/m3	
Oil mist, mineral (CAS 8012-95-1)	PEL	5 ppm 5 mg/m3	Mist.

ACGIH

Compounds Formed During Processing	Type	Value	Form
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction, as Al
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	TWA	0.05 mg/m3	(as Cr)
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.05 mg/m3	Soluble compounds as Cr
Ozone (CAS 10028-15-6)	TWA	0.2 ppm	(Heavy, moderate or light workloads (≤2 hours))

US ACGIH Threshold Limit Values: Short Term Exposure Limit (STEL): mg/m3

Compounds Formed During Processing	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3 & ppm

Compounds Formed During Processing	Type	Value	Form
Nitric oxide (CAS 10102-43-9)	TWA	25 ppm	
Nitrogen dioxide (CAS 10102-44-0)	TWA	0.2 ppm	

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
Lead‡ (CAS 7439-92-1)	TWA	0.05 mg/m3	
Manganese (CAS 7439-96-5)	TWA	0.1 mg/m3	Inhalable fraction.
Nickel† (CAS 7440-02-0)	TWA	0.02 mg/m3 1.5 mg/m3	Respirable fraction. Inhalable fraction.
Compounds Formed During Processing	Type	Value	Form
Chromium (III) compounds (CAS No. Not available)	TWA	0.5 mg/m3	
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	TWA	0.01 mg/m3	(as Cr)
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.01 mg/m3	Insoluble compounds as Cr
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Lead compounds, inorganic (CAS No. Not available)	TWA	0.05 mg/m3	

US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units

Compounds Formed During Processing	Type	Value	Form
Magnesium oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Manganese compounds, inorganic (CAS No. Not available)	TWA	0.1 mg/m3	Inhalable fraction.
Nickel compounds, insoluble (CAS No. Not available)	TWA	0.02 mg/m3	Respirable fraction.
		0.2 mg/m3	Inhalable fraction.
Oil mist, mineral (CAS 8012-95-1)	TWA	5 mg/m3	Inhalable fraction.
Zinc oxide (CAS 1314-13-2)	TWA	2 mg/m3	Respirable fraction.

Alcoa

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	3 mg/m3	Respirable fraction
		10 mg/m3	Total dust
Manganese (CAS 7439-96-5)	TWA	0.05 mg/m3	Total dust.
Nickel† (CAS 7440-02-0)	TWA	0.02 mg/m3	Respirable fraction.
		1 mg/m3	

Compounds Formed During Processing	Type	Value	Form
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Chromium (VI) compounds (CAS 18540-29-9)	TWA	0.25 µg/m3	
Manganese compounds, inorganic (CAS No. Not available)	TWA	0.05 mg/m3	Total dust, as Mn.
		0.02 mg/m3	Respirable fraction, as Mn.
Nickel compounds, insoluble (CAS No. Not available)	TWA	0.1 mg/m3	Insoluble
Oil mist, mineral (CAS 8012-95-1)	TWA	0.5 mg/m3	(8 Hour)

General

Personnel who handle and work with molten metal should utilize primary protective clothing like polycarbonate face shields, fire resistant tapper's jackets, neck shades (snoods), leggings, spats and similar equipment to prevent burn injuries. In addition to primary protection, secondary or day-to-day work clothing that is fire resistant and sheds metal splash is recommended for use with molten metal. Synthetic materials should never be worn even as secondary clothing (undergarments).

Minimize breathing oil vapors and mist. Remove oil contaminated clothing; launder or dry-clean before reuse. Remove oil contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at the end of the work period. Oil coating is readily removed from skin with waterless hand cleaners followed by a thorough washing with soap and water.

Sampling to establish lead level exposure is advised where exposure to airborne particulate or fumes is possible. Consult OSHA Lead Standard 29 CFR 1910.1025 for specific health/industrial hygiene precautions and requirements to follow when handling lead compounds.

Appropriate engineering controls

Dust and fumes from processing: Use with adequate explosion-proof ventilation designed to handle particulates to meet the limits listed in Section 8, Exposure Guidelines.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields. If molten: Goggles/face shield are recommended.

Skin protection	
Hand protection	Wear impervious gloves to avoid repeated or prolonged skin contact with residual oils and to avoid any skin injury.
Other	The need for personal protective equipment should be based upon a hazard assessment and recommendations from health / safety professionals.
Respiratory protection	Dust and fumes from processing: Use NIOSH-approved respiratory protection as specified by an Industrial Hygienist or other qualified professional if concentrations exceed the limits listed in Section 8. Suggested respiratory protection: P95, P100 for Lead.
Thermal hazards	Contact with molten material can cause thermal burns. Hot aluminum does not necessarily glow red. When material is heated, wear gloves to protect against thermal burns. Flame retardant protective clothing is recommended.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Form	Solid.
Color	Silver colored.
Odor	Odorless
Odor threshold	Not applicable
Density	2.70 - 2.75 g/cm ³ (0.098-0.099 lb/in ³)
Bulk density	Not applicable
pH	Not applicable
Melting point/freezing point	1149.8 - 1220 °F (621 - 660 °C)
Initial boiling point and boiling range	Not determined
Flash point	Not applicable
Evaporation rate	Not applicable
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - upper (%)	Not applicable
Flammability limit - lower (%)	Not applicable
Explosive properties	Dust can form an explosive mixture in air.
Dust explosion properties	
St class	Very strong explosion.
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	Not determined
Solubility(ies)	Insoluble
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Viscosity	Not applicable

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal conditions of use, storage, and transportation as shipped.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid

Chips, fines, dust and molten metal are considerably more reactive with the following:

- Water: Slowly generates flammable/explosive hydrogen gas and heat. Generation rate is greatly increased with smaller particles (e.g., fines and dusts). Molten metal can react violently/explosively with water or moisture, particularly when the water is entrapped.
- Heat: Oxidizes at a rate dependent upon temperature and particle size.

Explosions can occur with coils of foil that have been submerged or partially submerged in water for an extended period of time. Water can penetrate between the layers of foil, react with the aluminum surface and generate heat and hydrogen gas. When the coils are removed from the cooling effects of the water, rapid temperature increases can occur causing steam explosions which result in the rupture of the coils and discharge of debris.

Coils of foil may be a potential hazard under the following conditions:

- Coil has been annealed (annealing removes residual oil that could prevent penetration of water)
- Foil is very thin gauge (5-9 μm thickness which increases surface area)
- Coil has been immersed for an extended period of time (several hours or more)
- Wetted coil has recently been removed from the cooling effects of the water

In such situations, the coils should be isolated (30 meters from any personnel) for at least 72 hours as soon as possible after removal from the water. Coils making crackling sounds or emitting steam should not be approached or transported in commerce. Wetted coils should not be charged into a furnace for remelting until completely dry.

Incompatible materials

Chips, fines, dust and molten metal are considerably more reactive with the following:

- Acids and alkalis: Reacts to generate flammable/explosive hydrogen gas. Generation rate is greatly increased with smaller particles (e.g., fines and dusts).
- Strong oxidizers: Violent reaction with considerable heat generation. Can react explosively with nitrates (e.g., ammonium nitrate and fertilizers containing nitrate) when heated or molten.
- Halogenated compounds: Many halogenated hydrocarbons, including halogenated fire extinguishing agents, can react violently with finely divided or molten aluminum.
- Iron oxide (rust) and other metal oxides (e.g., copper and lead oxides): A violent thermite reaction generating considerable heat can occur. Reaction with aluminum fines and dusts requires only very weak ignition sources for initiation. Molten aluminum can react violently with iron oxide without external ignition source.
- Iron powder and water: Explosive reaction forming hydrogen gas when heated above 1470°F (800°C).

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Health effects associated with ingredients

Aluminum dust/fines and fumes: Low health risk by inhalation. Generally considered to be biologically inert (milling, cutting, grinding).

Manganese dust or fumes: Chronic overexposures: Can cause inflammation of the lung tissues, scarring of the lungs (pulmonary fibrosis), central nervous system damage, Secondary Parkinson's Disease and reproductive harm in males.

Silicon (inert dusts): Chronic overexposures: Can cause chronic bronchitis and narrowing of airways.

Chromium dust and fumes: Can cause irritation of eye, skin and respiratory tract. Metallic chromium and trivalent chromium: Not classifiable as to their carcinogenicity to humans by IARC.

Nickel dust and fume: Can cause irritation of eyes, skin and respiratory tract. Eye contact: Can cause inflammation of the eyes and eyelids (conjunctivitis). Skin contact: Can cause sensitization and allergic contact dermatitis. Chronic overexposures: Can cause perforation of the nasal septum, inflammation of the nasal passages (sinusitis), respiratory sensitization, asthma and scarring of the lungs (pulmonary fibrosis). Nickel alloys IARC/NTP: Reviewed and not recommended for listing by NTP. Listed as possibly carcinogenic to humans by IARC (Group 2B).

Lead dust or fume: Can cause irritation of eyes and upper respiratory tract. Acute overexposures: Can cause nausea and muscle cramps. Chronic overexposures: Can cause weakness in the extremities (peripheral neuropathy), abdominal cramps, gastrointestinal tract effects, kidney damage, liver damage, central nervous system damage, damage to the blood forming organs, blood cell damage and reproductive harm. Can cause reduced fertility and fetal toxicity in pregnant women. IARC/NTP: Listed as "reasonably anticipated to be a human carcinogen" by the NTP. Listed as possibly carcinogenic to humans by IARC (Group 2B).

Some products are supplied with an oil coating or have residual oil from the manufacturing process. Oil: Can cause irritation of skin. Skin contact (prolonged or repeated): Can cause dermatitis.

Health effects associated with compounds formed during processing

The following could be expected if welded, remelted or otherwise processed at elevated temperatures:

Alumina (aluminum oxide): Low health risk by inhalation. Generally considered to be biologically inert.

Zinc oxide fumes: Can cause irritation of upper respiratory tract. Acute overexposures: Can cause metal fume fever (nausea, fever, chills, shortness of breath and malaise).

Manganese oxide fumes: Can cause irritation of the eyes, skin, and respiratory tract. Acute overexposures: Can cause metal fume fever (nausea, fever, chills, shortness of breath and malaise). Chronic overexposures: Can cause inflammation of the lung tissues, scarring of the lungs (pulmonary fibrosis), central nervous system damage, Secondary Parkinson's Disease and reproductive harm in males.

Silica, amorphous: Acute overexposures: Can cause dryness of eyes, nose and upper respiratory tract.

Iron oxide: Chronic overexposures: Can cause benign lung disease (siderosis). Ingestion: Can cause irritation of gastrointestinal tract, bleeding, changes in the pH of the body fluids (metabolic acidosis) and liver damage.

Magnesium oxide fumes: Can cause irritation of the eyes and respiratory tract. Acute overexposures: Can cause metal fume fever (nausea, fever, chills, shortness of breath and malaise).

Chromium (III) compounds: Can cause irritation of eye, skin and respiratory tract. IARC/NTP: Not classifiable as to their carcinogenicity to humans by IARC.

Hexavalent chromium compounds (Chromium VI): Can cause irritation of eye, skin and respiratory tract. Skin contact: Can cause irritant dermatitis, allergic reactions and skin ulcers. Chronic overexposures: Can cause perforation of the nasal septum, respiratory sensitization, asthma, the accumulation of fluid in the lungs (pulmonary edema), lung damage, kidney damage, lung cancer, nasal cancer and cancer of the gastrointestinal tract. IARC/NTP: Listed as "known to be a human carcinogen" by the NTP. Listed as carcinogenic to humans by IARC (Group 1).

Nickel compounds: Associated with lung cancer, cancer of the vocal cords and nasal cancer. IARC/NTP: Listed as "known to be a human carcinogen" by the NTP. Listed as carcinogenic to humans by IARC (Group 1).

Lead (inorganic compounds): IARC/NTP: Listed as "reasonably anticipated to be a human carcinogen" by the NTP. Listed as probably carcinogenic to humans by IARC (Group 2A).

If the product is heated well above ambient temperatures or machined, oil vapor or mist may be generated.

Oil vapor or mist: Can cause irritation of respiratory tract. Acute overexposures: Can cause bronchitis, headache, central nervous system effects (nausea, dizziness and loss of coordination) and drowsiness (narcosis).

Welding, plasma arc cutting, and arc spray metalizing can generate ozone.

Ozone: Can cause irritation of eyes, nose and upper respiratory tract. Acute overexposures: Can cause shortness of breath, tightness of chest, headache, cough, nausea and narrowing of airways. Effects are reversible on cessation of exposure. Acute overexposures (high concentrations): Can cause respiratory distress, respiratory tract damage, bleeding and the accumulation of fluid in the lungs (pulmonary edema). Effects can be delayed up to 1-2 hours. Additional information: Studies (inhalation) with experimental animals have found genetic damage, reproductive harm, blood cell damage, lung damage and death.

Welding fumes: IARC/NTP: Listed as possibly carcinogenic to humans by IARC (Group 2B). Additional information: In one study, occupational asthma was associated with exposures to fumes from aluminum welding.

Plasma arc cutting of aluminum can generate oxides of nitrogen.

Oxides of nitrogen (NO and NO₂): Can cause irritation of eyes, skin and respiratory tract. Acute overexposures: Can cause reduced ability of the blood to carry oxygen (methemoglobin). Can cause cough, shortness of breath, accumulation of fluid in the lungs (pulmonary edema) and death. Effects can be delayed up to 2-3 weeks.

Nitrogen dioxide (NO₂): Chronic overexposures: Can cause scarring of the lungs (pulmonary fibrosis).

Information on likely routes of exposure

Eye contact Dust and fumes from processing: Can cause mechanical irritation.

Inhalation Dust: Can cause irritation of the upper respiratory tract.

Ingestion Not relevant, due to the form of the product.

Skin contact Dust and fumes from processing: Can cause irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dust and fume from processing: Can cause irritation of the upper respiratory tract. Heating above the melting point releases metallic oxides which may cause metal fume fever by inhalation. The symptoms are shivering, fever, malaise and muscular pain. Contains nickel. May produce an allergic reaction.

Information on toxicological effects

Acute toxicity Not classified. Based on available data, the classification criteria are not met.

Components	Species	Test Results
Aluminum (CAS 7429-90-5)		
Acute <i>Inhalation</i> LC50	Rat	> 2.3 mg/l 7.6 mg/l
<i>Oral</i> LD50	Rat	> 2000 mg/kg
Nickel† (CAS 7440-02-0)		
Acute <i>Oral</i> LD50	Rat	> 9000 mg/kg
Zinc (CAS 7440-66-6)		
Acute <i>Oral</i> LD50	Rat	630 mg/kg
Compounds Formed During Processing	Species	Test Results
Aluminum oxide (non-fibrous) (CAS 1344-28-1)		
Acute <i>Inhalation</i> LC50	Rat	> 2.3 mg/l 7.6 mg/l
<i>Oral</i> LD50	Rat	> 5000 mg/kg
Iron oxide (CAS 1309-37-1)		
Acute <i>Oral</i> LD50	Rat	> 10000 mg/kg
Nitric oxide (CAS 10102-43-9)		
Acute <i>Inhalation</i> LC50	Rat	115 mg/l, 1 Hours 57.5 mg/l, 4 Hours
Nitrogen dioxide (CAS 10102-44-0)		
Acute <i>Inhalation</i> LC50	Guinea pig Rat	30 ppm, 1 Hours 88 ppm, 4 Hours
Silica, amorphous (CAS 69012-64-2)		
Acute <i>Oral</i> LD50	Mouse Rat	> 15000 mg/kg > 22500 mg/kg
Zinc oxide (CAS 1314-13-2)		
Acute <i>Inhalation</i> LC50	Mouse	> 5.7 mg/l, 4 Hours
<i>Oral</i> LD50	Mouse	7950 mg/kg

Compounds Formed During Processing	Species	Test Results
	Rat	> 5000 mg/kg > 5 g/kg
<i>Other</i> LD50	Rat	240 mg/kg
Skin corrosion/irritation	Dust and fume from processing: Non-corrosive.	
Serious eye damage/eye irritation	Dust in the eyes: May cause minor irritation on eye contact.	
Respiratory or skin sensitization	Not classified. Based on available data, the classification criteria are not met.	
Respiratory sensitization	Not classified. Based on available data, the classification criteria are not met.	
Skin sensitization	Dust and fume from processing: Can cause mechanical irritation. Contains nickel. May produce an allergic reaction.	
Germ cell mutagenicity	Not classified. Based on available data, the classification criteria are not met.	
Neurological effects	Not classified. Based on available data, the classification criteria are not met.	
Pre-existing conditions aggravated by exposure	Asthma, chronic lung disease, and skin rashes.	
Carcinogenicity	Product as shipped: Does not present any cancer hazards. Dust from mechanical processing: Dust and fumes from welding or elevated temperature processing: Can present a cancer hazard (Hexavalent chromium compounds, Lead compounds, Nickel compounds, Welding fumes).	
ACGIH Carcinogens		
Aluminum (CAS 7429-90-5)		A4 Not classifiable as a human carcinogen.
Aluminum oxide (non-fibrous) (CAS 1344-28-1)		A4 Not classifiable as a human carcinogen.
Chromium (CAS 7440-47-3)		A4 Not classifiable as a human carcinogen.
Chromium (III) compounds (CAS No. Not available)		A4 Not classifiable as a human carcinogen.
Chromium (VI) compounds (CAS 18540-29-9)		A1 Confirmed human carcinogen.
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)		A1 Confirmed human carcinogen.
Chromium (VI) compounds, water soluble forms (CAS No. Not available)		A1 Confirmed human carcinogen.
Iron oxide (CAS 1309-37-1)		A4 Not classifiable as a human carcinogen.
Lead compounds, inorganic (CAS No. Not available)		A3 Confirmed animal carcinogen with unknown relevance to humans.
Lead‡ (CAS 7439-92-1)		A3 Confirmed animal carcinogen with unknown relevance to humans.
Magnesium oxide (CAS 1309-48-4)		A4 Not classifiable as a human carcinogen.
Manganese (CAS 7439-96-5)		A4 Not classifiable as a human carcinogen.
Nickel compounds, insoluble (CAS No. Not available)		A1 Confirmed human carcinogen.
Nickel† (CAS 7440-02-0)		A5 Not suspected as a human carcinogen.
Nitrogen dioxide (CAS 10102-44-0)		A4 Not classifiable as a human carcinogen.
Oil mist, mineral (CAS 8012-95-1)		A2 Suspected human carcinogen.
Ozone (CAS 10028-15-6)		A4 Not classifiable as a human carcinogen.
IARC Monographs. Overall Evaluation of Carcinogenicity		
Chromium (CAS 7440-47-3)		3 Not classifiable as to carcinogenicity to humans.
Chromium (III) compounds (CAS No. Not available)		3 Not classifiable as to carcinogenicity to humans.
Chromium (VI) compounds (CAS 18540-29-9)		1 Carcinogenic to humans.
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)		1 Carcinogenic to humans.
Chromium (VI) compounds, water soluble forms (CAS No. Not available)		1 Carcinogenic to humans.
Iron oxide (CAS 1309-37-1)		3 Not classifiable as to carcinogenicity to humans.
Lead compounds, inorganic (CAS No. Not available)		2A Probably carcinogenic to humans.
Lead‡ (CAS 7439-92-1)		2B Possibly carcinogenic to humans.
Nickel compounds, insoluble (CAS No. Not available)		1 Carcinogenic to humans.
Nickel† (CAS 7440-02-0)		1 Carcinogenic to humans.
Silica, amorphous (CAS 69012-64-2)		3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Chromium (VI) compounds (CAS 18540-29-9)	Known To Be Human Carcinogen.
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Known To Be Human Carcinogen.
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Known To Be Human Carcinogen.
Lead compounds, inorganic (CAS No. Not available)	Reasonably Anticipated to be a Human Carcinogen.
Lead‡ (CAS 7439-92-1)	Reasonably Anticipated to be a Human Carcinogen.
Nickel† (CAS 7440-02-0)	Known To Be Human Carcinogen.
	Reasonably Anticipated to be a Human Carcinogen.
Oil mist, mineral (CAS 8012-95-1)	Known To Be Human Carcinogen.

Reproductive toxicity	Product as shipped: Does not present any reproductive hazards.
	Dust from mechanical processing: Can present a reproductive hazard (Lead).
	Dust and fumes from welding or elevated temperature processing: Can present a reproductive hazard (Lead compounds, Manganese compounds).
Teratogenicity	Not classified. Based on available data, the classification criteria are not met.
Specific target organ toxicity - single exposure	Not classified. Based on available data, the classification criteria are not met.
Specific target organ toxicity - repeated exposure	Not classified. Based on available data, the classification criteria are not met.
Aspiration hazard	Not applicable.
Further information	None known.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Components	Species	Test Results
Chromium (CAS 7440-47-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 0.01 - 0.7 mg/l, 48 hours
Fish	LC50	Carp (Cyprinus carpio) 14.3 mg/l, 96 hours
Iron (CAS 7439-89-6)		
Aquatic		
Crustacea	LC50	Cockle (Cerastoderma edule) 100 - 330 mg/l, 48 hours
		Common shrimp, sand shrimp (Crangon crangon) 33 - 100 mg/l, 48 hours
Fish	LC50	Channel catfish (Ictalurus punctatus) > 500 mg/l, 96 hours
Lead‡ (CAS 7439-92-1)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 1.17 mg/l, 96 hours
Manganese (CAS 7439-96-5)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 40 mg/l, 48 hours
Nickel† (CAS 7440-02-0)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 2.923 mg/l, 96 hours
Zinc (CAS 7440-66-6)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 2.8 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.56 mg/l, 96 hours

Compounds Formed During Processing	Species	Test Results
Nitrogen dioxide (CAS 10102-44-0)		
Aquatic		
Fish	LC50	Tench (Tinca tinca) 19.6 mg/l, 96 hours
Ozone (CAS 10028-15-6)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.0081 - 0.0106 mg/l, 96 hours
Zinc oxide (CAS 1314-13-2)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 2246 mg/l, 96 hours

Persistence and degradability	Not inherently biodegradable.
Bioaccumulative potential	The product is not bioaccumulating.
Mobility in soil	Not considered mobile.
Mobility in general	Not applicable.
Other adverse effects	Not available.

13. Disposal considerations

Disposal instructions	Reuse or recycle material whenever possible. If reuse or recycling is not possible, disposal must be made according to local or governmental regulations.
Waste codes	RCRA Status: Must be determined at the point of waste generation. If material is disposed as a waste, it must be characterized under RCRA according to 40 CFR, Part 261, or state equivalent in the U.S. TCLP testing is recommended for Chromium and Lead in a waste disposal scenario.

US RCRA Hazardous Waste P List: Reference

Nitric oxide (CAS 10102-43-9)	P076
Nitrogen dioxide (CAS 10102-44-0)	P078

Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

General Shipping Information

Basic Shipping Information

ID number	-
Proper shipping name	Not regulated
Hazard class	-
Packing group	-

General Shipping Notes

- When "Not regulated", enter the proper freight classification, SDS Number and Product Name onto the shipping paperwork.

Disclaimer

This section provides basic classification information and, where relevant, information with respect to specific modal regulations, environmental hazards and special precautions. Otherwise, it is presumed that the information is not available/not relevant

15. Regulatory information

US federal regulations	In reference to Title VI of the Clean Air Act of 1990, this material does not contain nor was it manufactured using ozone-depleting chemicals. All electrical equipment must be suitable for use in hazardous atmospheres involving aluminum powder in accordance with 29 CFR 1910.307. The National Electrical Code, NFPA 70, contains guidelines for determining the type and design of equipment and installation which will meet this requirement.
-------------------------------	---

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chromium (VI) compounds (CAS 18540-29-9)	0.1 % Annual Export Notification required.
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	0.1 % Annual Export Notification required.
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	0.1 % Annual Export Notification required.

CERCLA Hazardous Substance List (40 CFR 302.4)

Chromium (CAS 7440-47-3)	LISTED
Chromium (II) compounds (CAS No. Not available)	LISTED
Chromium (III) compounds (CAS No. Not available)	LISTED
Chromium (VI) compounds (CAS 18540-29-9)	LISTED
Lead compounds, inorganic (CAS No. Not available)	LISTED
Lead‡ (CAS 7439-92-1)	LISTED
Manganese (CAS 7439-96-5)	LISTED
Manganese compounds, inorganic (CAS No. Not available)	LISTED
Nickel compounds, insoluble (CAS No. Not available)	LISTED
Nickel† (CAS 7440-02-0)	LISTED
Nitric oxide (CAS 10102-43-9)	LISTED
Nitrogen dioxide (CAS 10102-44-0)	LISTED
Zinc (CAS 7440-66-6)	LISTED
Zinc oxide (CAS 1314-13-2)	LISTED

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity

Nitric oxide (CAS 10102-43-9)	10 LBS
Nitrogen dioxide (CAS 10102-44-0)	10 LBS
Ozone (CAS 10028-15-6)	100 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chromium (VI) compounds (CAS 18540-29-9)	Cancer
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Cancer
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Cancer
Lead compounds, inorganic (CAS No. Not available)	Reproductive toxicity
Lead‡ (CAS 7439-92-1)	Reproductive toxicity
Chromium (VI) compounds (CAS 18540-29-9)	Eye irritation
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Eye irritation
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Eye irritation
Lead compounds, inorganic (CAS No. Not available)	Central nervous system
Lead‡ (CAS 7439-92-1)	Central nervous system
Chromium (VI) compounds (CAS 18540-29-9)	Skin sensitization
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Skin sensitization
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Skin sensitization
Lead compounds, inorganic (CAS No. Not available)	Kidney
Lead‡ (CAS 7439-92-1)	Kidney
Lead compounds, inorganic (CAS No. Not available)	Blood
Lead‡ (CAS 7439-92-1)	Blood
Lead compounds, inorganic (CAS No. Not available)	Acute toxicity
Lead‡ (CAS 7439-92-1)	Acute toxicity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories	Immediate Hazard - Yes	If particulates/fumes generated during processing
	Delayed Hazard - Yes	If particulates/fumes generated during processing
	Fire Hazard - No	
	Pressure Hazard - No	
	Reactivity Hazard - Yes	If molten

SARA 302 Extremely hazardous substance Yes

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum	7429-90-5	>92
Zinc	7440-66-6	<2.8
Manganese	7439-96-5	<2
Nickel†	7440-02-0	<0.1
Lead‡	7439-92-1	<0.1

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Aluminum (CAS 7429-90-5)
 Aluminum oxide (non-fibrous) (CAS 1344-28-1)
 Chromium (CAS 7440-47-3)
 Iron oxide (CAS 1309-37-1)
 Lead‡ (CAS 7439-92-1)
 Magnesium (CAS 7439-95-4)
 Magnesium oxide (CAS 1309-48-4)
 Manganese (CAS 7439-96-5)
 Nickel† (CAS 7440-02-0)
 Nitric oxide (CAS 10102-43-9)
 Nitrogen dioxide (CAS 10102-44-0)
 Oil mist, mineral (CAS 8012-95-1)
 Ozone (CAS 10028-15-6)
 Silicon (CAS 7440-21-3)
 Zinc (CAS 7440-66-6)
 Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum (CAS 7429-90-5)	500 LBS
Aluminum oxide (non-fibrous) (CAS 1344-28-1)	500 LBS
Chromium (CAS 7440-47-3)	500 LBS
Chromium (II) compounds (CAS No. Not available)	500 LBS
Chromium (III) compounds (CAS No. Not available)	500 LBS
Chromium (VI) compounds (CAS 18540-29-9)	500 LBS
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	500 LBS
Lead compounds, inorganic (CAS No. Not available)	500 LBS
Lead‡ (CAS 7439-92-1)	500 LBS
Manganese (CAS 7439-96-5)	500 LBS
Manganese compounds, inorganic (CAS No. Not available)	500 LBS
Nickel compounds, insoluble (CAS No. Not available)	500 LBS
Nickel† (CAS 7440-02-0)	500 LBS
Nitric oxide (CAS 10102-43-9)	100 LBS
Nitrogen dioxide (CAS 10102-44-0)	100 LBS
Ozone (CAS 10028-15-6)	100 LBS
Zinc (CAS 7440-66-6)	500 LBS
Zinc oxide (CAS 1314-13-2)	500 LBS

US. Pennsylvania RTK - Hazardous Substances

Aluminum (CAS 7429-90-5)
 Aluminum oxide (non-fibrous) (CAS 1344-28-1)
 Chromium (CAS 7440-47-3)
 Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)
 Chromium (VI) compounds, water soluble forms (CAS No. Not available)
 Iron oxide (CAS 1309-37-1)
 Lead‡ (CAS 7439-92-1)
 Magnesium (CAS 7439-95-4)
 Magnesium oxide (CAS 1309-48-4)
 Manganese (CAS 7439-96-5)
 Nickel† (CAS 7440-02-0)
 Nitric oxide (CAS 10102-43-9)
 Nitrogen dioxide (CAS 10102-44-0)
 Oil mist, mineral (CAS 8012-95-1)
 Ozone (CAS 10028-15-6)
 Silica, amorphous (CAS 69012-64-2)
 Silicon (CAS 7440-21-3)
 Zinc (CAS 7440-66-6)
 Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Aluminum (CAS 7429-90-5)
 Aluminum oxide (non-fibrous) (CAS 1344-28-1)

Chromium (CAS 7440-47-3)
 Chromium (II) compounds (CAS No. Not available)
 Chromium (VI) compounds (CAS 18540-29-9)
 Chromium (VI) compounds, water soluble forms (CAS No. Not available)
 Lead compounds, inorganic (CAS No. Not available)
 Lead‡ (CAS 7439-92-1)
 Manganese (CAS 7439-96-5)
 Manganese compounds, inorganic (CAS No. Not available)
 Nickel compounds, insoluble (CAS No. Not available)
 Nickel† (CAS 7440-02-0)
 Nitric oxide (CAS 10102-43-9)
 Nitrogen dioxide (CAS 10102-44-0)
 Ozone (CAS 10028-15-6)
 Zinc (CAS 7440-66-6)
 Zinc oxide (CAS 1314-13-2)

US. California Proposition 65

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Chromium (VI) compounds (CAS 18540-29-9)	Listed: February 27, 1987
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Listed: February 27, 1987
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Listed: February 27, 1987
Lead compounds, inorganic (CAS No. Not available)	Listed: October 1, 1992
Lead‡ (CAS 7439-92-1)	Listed: October 1, 1992
Nickel compounds, insoluble (CAS No. Not available)	Listed: May 7, 2004
Nickel† (CAS 7440-02-0)	Listed: May 7, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Chromium (VI) compounds (CAS 18540-29-9)	Listed: December 19, 2008
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Listed: December 19, 2008
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Listed: December 19, 2008
Lead compounds, inorganic (CAS No. Not available)	Listed: February 27, 1987
Lead‡ (CAS 7439-92-1)	Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Chromium (VI) compounds (CAS 18540-29-9)	Listed: December 19, 2008
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Listed: December 19, 2008
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Listed: December 19, 2008
Lead compounds, inorganic (CAS No. Not available)	Listed: February 27, 1987
Lead‡ (CAS 7439-92-1)	Listed: February 27, 1987

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Chromium (VI) compounds (CAS 18540-29-9)	Listed: December 19, 2008
Chromium (VI) compounds, certain water insoluble forms (CAS No. Not available)	Listed: December 19, 2008
Chromium (VI) compounds, water soluble forms (CAS No. Not available)	Listed: December 19, 2008
Lead compounds, inorganic (CAS No. Not available)	Listed: February 27, 1987
Lead‡ (CAS 7439-92-1)	Listed: February 27, 1987

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

SDS Status March 8, 2015: Change(s) in Section: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 and 16.
 March 18, 2013: Change(s) in Section: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 15 and 16.
 December 3, 2009: New format.
 September 28, 2006: Reviewed on a periodic basis in accordance with Alcoa policy. Change(s) in Section: 1, 2, 3, 4, 5, 7, 8, 9, 10, 11, 12 and 15.
 August 14, 2003: Reviewed on a periodic basis in accordance with Alcoa policy. Change(s) in Section: 1, 2, 3, 8 and 15.
 Origination date: March 16, 1990

SDS System Number: 115951

Revision date March 8, 2015.

Version # 07

Further information Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Revision Information Product and Company Identification: Synonyms
 Hazards Identification: US Hazardous
 Composition / Information on Ingredients: Ingredients
 Physical & Chemical Properties: Multiple Properties
 Transport Information: Agency Name, Packaging Type, and Transport Mode Selection
 Regulatory Information: United States
 GHS: Classification

Disclaimer The information in the sheet was written based on the best knowledge and experience currently available.

Other information

- Guide to Occupational Exposure Values 2014, Compiled by the American Conference of Governmental Industrial Hygienists (ACGIH).
- NIOSH Pocket Guide to Chemical Hazards, U.S. Department of Health and Human Services, September 2005.
- TOXNET, U.S. National Library of Medicine
- expub, Expert Publishing, LLC., www.expub.com,
- Ariel, 3E Company, www.3Ecompany.com
- Aluminum Association's Bulletin F-1, "Guidelines for Handling Aluminum Fines Generated During Various Aluminum Fabricating Operations." The Aluminum Association, 1525 Wilson Boulevard, Suite 600, Arlington, Virginia 22209, www.aluminum.org.
- Aluminum Association, "Guidelines for Handling Molten Aluminum, The Aluminum Association, 1525 Wilson Boulevard, Suite 600, Arlington, Virginia 22209, www.aluminum.org.
- NFPA 484, Standard for Combustible Metals (NFPA phone: 800-344-3555)
- NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids
- NFPA 70, Standard for National Electrical Code (Electrical Equipment, Grounding and Bonding)
- NFPA 77, Standard for Static Electricity
- NFPA 68, Standard on Explosion Protection by Deflagration Venting,
- NFPA 69, Standard on Explosion Prevention System

Key/Legend:

ACGIH American Conference of Governmental Industrial Hygienists
AICS Australian Inventory of Chemical Substances
CAS Chemical Abstract Services
CERCLA Comprehensive Environmental Response, Compensation, and Liability Act
CFR Code of Federal Regulations
CPR Cardio-pulmonary Resuscitation
DOT Department of Transportation
DSL Domestic Substances List (Canada)
EC Effective Concentration
ED Effective Dose
EINECS European Inventory of Existing Commercial Chemical Substances
ENCS Japan - Existing and New Chemical Substances
EWC European Waste Catalogue
EPA Environmental Protective Agency
IARC International Agency for Research on Cancer
LC Lethal Concentration
LD Lethal Dose
MAK Maximum Workplace Concentration (Germany) "maximale Arbeitsplatz-Konzentration"
NDSL Non-Domestic Substances List (Canada)
NIOSH National Institute for Occupational Safety and Health
NTP National Toxicology Program
OEL Occupational Exposure Limit
OSHA Occupational Safety and Health Administration
PIN Product Identification Number
PMCC Pensky Marten Closed Cup
RCRA Resource Conservation and Recovery Act
SARA Superfund Amendments and Reauthorization Act
SIMDUT Système d'Information sur les Matières Dangereuses Utilisées au Travail
STEL Short Term Exposure Limit
TCLP Toxic Chemicals Leachate Program
TDG Transportation of Dangerous Goods
TLV Threshold Limit Value
TSCA Toxic Substances Control Act
TWA Time Weighted Average
WHMIS Workplace Hazardous Materials Information System
m meter, cm centimeter, mm millimeter, in inch,
g gram, kg kilogram, lb pound, µg microgram,
ppm parts per million, ft feet

*** End of SDS ***

WROUGHT ALUMINUM PRODUCTS, 3XXX SERIES ALLOYS

Hazard statement

May form combustible dust concentrations in air.

Precautionary statement

Prevention
Not applicable.

Response
Not applicable.

Storage
Not applicable.

Disposal
Reuse or recycle material whenever possible. Dispose of contents/container in accordance with local/regional/national/international regulations.

Warning

Supplemental information

Non-combustible as supplied. Small chips, fine turnings and dust from processing may be readily ignitable.

Explosion/fire hazards may be present when:

- Dust or fines are dispersed in air.
- Chips, dust or fines are in contact with water.
- Dust and fines are in contact with certain metal oxides (e.g., rust, copper oxide).
- Molten metal in contact with water/moisture or certain metal oxides (e.g., rust, copper oxide).

FIRE FIGHTING MEASURES: Use Class D extinguishing agents on fines, dust or molten metal. Use coarse water spray on chips and turnings.

DO NOT USE halogenated extinguishing agents on small chips/fines.

DO NOT USE water in fighting fires around molten metal.

These fire extinguishing agents will react with the burning material.

IN CASE OF SPILL: Collect scrap for recycling, if molten. Use dry sand to contain the flow of material. All tooling (e.g., shovels or hand tools) and containers which come in contact with molten metal must be preheated or specially coated, rust free and approved for such use. Allow the spill to cool before remelting as scrap.

See Alcoa SDS Number 0665.

USA: Chemtrec: +1-703-527-3887 +1-800-424-9300 (24 Hour Emergency Telephone, multiple languages spoken)

Alcoa Inc., 201 Isabella Street, Pittsburgh, PA 15212-5858 United States +1-412-553-4001 (24 Hour Emergency Telephone, English only)
Alcoa Health and Safety Email: accmsds@alcoa.com Tel: +1-412-553-4649 and Fax: +1-412-553-4822

